



# UTP101P-IV

Balun video pasiv cu protectie si bloc terminal tip "push"

## Imagine

UTEPO



## Descriere

Balun video pasiv pentru sistemele de supraveghere video analogice, cu protectie si bloc terminat de tip "push". Protectie la supratensiune de 2 kV. Compatibil cu sistemele: PAL, NTSC, SECAM. Mufa BNC montata in carcasa.

## Caracteristici

- Nu necesita alimentare
- Transmisie in timp real a semnalului video
- Transferul unui canal video prin cablu UTP CAT5e/6
- Protectie la supratensiuni, descarcari electrostatice
- Mufa BNC montata in carcasa

## Specificatii

- Canale transmisie: 1 canal video
- Conector video: BNC/Bloc terminal rapid (push)
- Distanța transmisie: Pana la 900 m (cu balun activ)  
300 m (cu balun pasiv)
- Formate compatibile: PAL, NTSC, SECAM
- Latime de banda semnal: 0~6 MHz (-3db)
- Atenuarea interferentelor: > 60 db
- Protectie supratens. coaxial: 4kV, per IEC 61000-4-5
- Protectie supratens. UTP: 2 kV (diferentiala), 4KV (comuna), Per: IEC 61000-4-5
- ESD: Descarcare la contact: 6KV  
Descarcare prin aer: 8KV  
Per: IEC 61000-4-2
- Durata medie de viata: > 10000 h
- Temperatura de lucru: - 10 °C ~ +55 °C
- Temperatura de stocare: - 40 °C ~ +85 °C
- Umiditate: 0~95% (fara condensare)
- Material: ABS, Negru
- Dimensiuni: 39(L) x 20(l) x 15(H) mm
- Greutate: 28 g

## Aplicatie



YLI ETERNIT ACCES SRL  
A.: HAIDUCULUI 3A, CLUJ-NAPOCA  
T.: +40 264 484989  
W.: www.yli.ro

UTP101P-IV  
Balun video pasiv cu protectie si  
bloc terminal tip "push"  
FISA TEHNICA

## Observatii



EEE FAC OBIECTUL UNEI  
COLECTARI SEPARATE

