



IDR-C2MF-SA

Cititor USB carduri de proximitate MIFARE MF 13.56 MHz

YLI ETERNIT ACCES SRL
A.: HAIDUCULUI 3A, CLUJ-NAPOCA
T.: +40 264 484989
W.: www.yli.ro

IDR-C2MF-SA
Cititor USB carduri de proximitate
MIFARE MF 13.56 MHz
FISA TEHNICA

Imagine



Descriere

IDR-C2MF-SA este un cititor de proximitate cu USB pentru carduri de proximitate MIFARE MF 13.56 MHz, Standart ISO 14443A.

Caracteristici

- Iesire: 6H10D initial (26bit), ajustabil la cerere
- 6H, 8H, 10H, 5H10D, 6H10D, 8H10D, 10H10D, 2H10D+4H10D, 4H10D+4H10D, 6H10D/8H10D (ultimele 8 cifre), M8H/M8H10D (revers)
- Interfata USB
- Alimentare prin USB
- Citeste cartele/taguri de proximitate MF 13.56 MHz
- Led indicator stare si buzzer
- Nu necesita instalare de driver
- Compatibil cu Windows 98, 2000, XP, Vista, 7 si 8

Specificatii

- | | |
|-------------------------------|----------------------------|
| • Alimentare USB: | 5Vcc / 100mA |
| • Carduri compatibile: | MF 13.56 MHz |
| • Distanța de citire: | < 10 cm |
| • Material: | ABS, negru |
| • Umiditate relativa: | 10% ~ 90%, fara condensare |
| • Temperatura de functionare: | -10°C ~ +70°C |
| • Dimensiuni: | 100(L) x 68(l) x 11(H) mm |
| • Masa neta: | 80 g |

Observatii



EEE FAC OBIECTUL UNEI
COLECTARI SEPARATE

