



UTP101P-HD6

Balun video HD pasiv cu protectie si buton de tip "push"

Imagine

UTEPO



YLI ETERNIT ACCES SRL
A.: HAIDUCULUI 3A, CLUJ-NAPOCA
T.: +40 264 484989
W.: WWW.YLI.RO

UTP101P-HD6
Balun video HD pasiv cu protectie si buton
de tip "push"
FISA TEHNICA

Descriere



Balun video HD pasiv pentru sistemele de supraveghere video analogice HD. Echipat cu buton de tip "push", ceea ce faciliteaza instalarea.

Protectie la supratensiune pe cablu 2 kV. Compatibil cu sistemele: HDTV, AHD, HDCVI, analog SD.

Distanta de transmisie de pana la 500m folosit cu un balun pasiv, si pana la 650m folosit cu un balun activ.

Caracteristici

- Nu necesita alimentare
- Transmite in timp real semnal video 720P / 1080P
- Transferul unui canal video HD prin cablu UTP CAT5e/6
- Protectie la supratensiuni, descarcari electrostatice, ESD
- Design inovativ
- Buton de tip "push"
- Plug-and-play

Specificatii

- Canale transmisie: 1 canal video
- Conector video: BNC
- Distanta transmisie:
 - HDCVI:** 300m / 720P, 250 / 1080P
4MP / 200m, 8MP / 150m
 - HDTV:** 200m / 720P, 250m / 1080P
3MP / 250m, 5MP / 150m, 8MP / 150m
 - AHD:** 200m / 720P-960P, 300m / 1080P
4MP / 200m, 5MP / 150m
 - Analog Video:** 500 m
- Formate compatibile: HDCVI, AHD, HDTV, analog SD
- Latime de banda semnal: 0-75 MHz
- Protectie supratens. coaxial: 2 kV, per IEC 61000-4-5
- Protectie supratensiune UTP: 2 kV, per IEC 61000-4-5
- Impedanta: BNC 75 ohm
- Durata medie de viata: > mai mult de 10000 h
- Temperatura de lucru: - 10 °C ~ 55 °C
- Temperatura de stocare: - 40 °C ~ 85 °C
- Umiditate: 0 ~ 95% (fara condensare)
- Material: ABS, Negru
- Dimensiuni: 35(L) x 19(l) x 15(H) mm
- Masa bruta: 50 g

Aplicatie



Observatii



EEE FAC OBJEKTUL UNEI
COLECTARI SEPARATE

