



NFC-2013-gy

Tag NFC, cu cip NXP NTAG213

Imagine



Descriere

NFC-2013-gy este un tag NFC, rotund, cu cip Cip NXP NTAG213.
Frecventa de functionare de 13.56 MHz.

Caracteristici

- Tag NFC
- Cip NXP MIFARE Ultralight (Ultralight C) - NTAG213, read/write
- Format Wiegand 34
- Protocol anti-coliziune
- Protectie la scriere (parola)
- Parole pe 32 biti
- UID ASCII mirrors
- Contoare de 24 biti

Specificatii

- | | |
|----------------------------------|------------------------------------|
| • Frecventa de operare: | 13.56MHz |
| • Viteza de transfer: | 106kbit/s |
| • Distanța de citire: | 100mm (depinde de cititor) |
| • Serial number: | 7biti |
| • Capacitor: | 50pF |
| • Memorie: | 180biti organizata in 45 de pagini |
| • Memorie pentru scriere/citire: | 137biti |
| • Retinere date: | 10ani |
| • Material: | ABS |
| • Forma: | Rotund |
| • Temperatura de operare: | -40 ~ +85°C |
| • Culoare: | Gri |
| • Dimensiuni: | 40(L) x 34(l) x 4(A) mm |
| • Greutate: | 5g |

YLI ETERNIT ACCES SRL
A.: HAIDUCULUI 3A, CLUJ-NAPOCA
T.: +40 264 484989
W.: www.yli.ro

NFC-2013-gy
Tag NFC, cu cip NXP NTAG213
FISA TEHNICA

Observatii



EEE FAC OBIECTUL UNEI
COLECTARI SEPARATE

