

# UTP701E

Injector POE, 802.3af  
10/100/1000Mbps

## DESCRIERE

Injector POE pentru alimentarea dispozitivelor compatibile POE folosind cablul de date. Suporta conexiuni de date de pana la 1Gbps si o putere maxima de iesire de 15.4W (conform standard IEEE802.3af - POE clasa 3)

## CARACTERISTICI

Alimentare incorporata, 100-240Vca, 50/60Hz

Putere de iesire de pana la 15.4W

Distanta de transmisie/alimentare: 100m (CAT5e/6)

Standard IEEE802.3af (48Vcc, max. 15.4W)

Protectie la: variatii mari de tensiune de alimentare, ESD, interferente


Montare pe perete sau pe masa, mai multe adaptoare pot fi unite

## SPECIFICATII

Alimentare POE	Alimentare	Retea, conector C14
	Tensiune de alimentare	Vac100V~240V
	Putere de iesire	≤15.4W@48Vcc
Retea	Porturi comunicatie	1xRJ45 IN / 1xRJ45 OUT
	Rata de transmisie	10/100Mbps,10/100/1000Mbps
	Mediu de transmisie	Cablu CAT5/5e/6
	Distanta	100m(Max)
Status	LED Alimentare	1(Verde)
	LED POE	1 (Galben)
Protectie	Protectie la supratensiuni	1KV Per: IEC61000-4-5
	ESD	1a Descarcare la contact nivel 3 1b Descarcare prin aer nivel 3 Per: IEC61000-4-2
Mediu	Temperatura de lucru	0°C~55°C
	Temperatura de stocare	-20°C~70°C
	Umiditate	0~90%
Mecanica	Dimensiuni	120mm×62mm×39mm
	Material	ABS
	Culoare	Negru
	Greutate	200g
Stabilitate	MTBF	>30000h



Fata



Sparte



Interconectare folosind baioneta

## Fisa tehnica



YLI ETERNIT ACCES Srl

A.: Str. Haiducului 3A  
400040 Cluj-Napoca  
Romania

T.: 004 0264 484 989  
F.: 004 0364 262 990  
W.: www.yli.ro