



GNT-P4824T

Splitter PoE destinat alimentarii Access Point-urilor, standard 802.3af/at, iesire POE pasiv 24VCC/1A, 10/100 Mbps

Imagine



Descriere

Splitter PoE destinat alimentarii Access Point-urilor, compatibil cu standardele IEEE 802.3af/at, care preia alimentarea PoE si furnizeaza la iesire PoE pasiv 24VDC/1A prin interfata RJ45, asigurand simultan transmisia de date la viteze de 10/100 Mbps.

Caracteristici

- Compatibil cu standardele PoE IEEE 802.3af/at, pana la 30 W
- Iesire alimentare 24V / 1A prin RJ45
- Suporta transmisie date 10/100 Mbps pe portul PoE
- Detecteaza automat alimentarea de la modulul PSE
- Protectie la scurtcircuit si supratensiune

Specificatii

- Rata de transfer: 10/100Mbps
- Tensiune de intrare: 44~57Vcc
- Tensiunea de iesire: min. 23.5V /tipic 24V/ max. 24.5V
- Standard PoE: IEEE 802.3af/at, max. 30W
- Standarde retea: IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af/at
- LED-uri: Galben: 24V; Verde: Class 4
- Protectie: Scurtcircuit, supratensiune
- Temperatura de lucru: -40°C - +70°C
- Dimensiuni: 80.3 × 28.3 × 23.2 mm
- Greutate: 0.2 kg

YLI ETERNIT ACCES srl

A.: HAIDUCULUI 3A, CLUJ-NAPOCA

T.: +40 264 484989

W.: www.yli.ro

GNT-P4824T

Splitter PoE destinat alimentarii Access Point-urilor, standard 802.3af/at, iesire POE pasiv 24VCC/1A, 10/100 Mbps

FISA TEHNICA

Observatii



EEE FAC OBIECTUL UNEI
COLECTARI SEPARATE

